



REFRIGERATION

SERVING THE FOOD INDUSTRY SINCE 1951

54" Top Mounted 2 Door Reach-in Freezer 115V/60Hz/1Ph cETLus ETL Sanitation Energy Star

ITEM:

50117

MODEL: FR-CN-0054-TM



Perfect freezer for storage and back of house usage.

Spacious stainless steel freezer crafted with enduring quality. Sleek design featuring two self closing doors, high-efficiency components, and a wide handle. Ideal for back of house kitchen operations and storage.

FEATURES:

· 6 Shelves

6 plastic coated shelves with 88lb loading capacity

· Energy Star Certified

Energy star certified for economical and environmentally friendly consumption.

· Self Closing Doors

Equipped withself closing doors to prevent loss of efficiency from the door being left open accidentally

Automatic Defrost System

The appliance automatically defrosts to avoid ice build-up and lengthens lifespan

LED Lighting System

Our LED system uses a fraction of the energy of regular fluorescent lights and requires no replacement for up seven years.

Telephone: 1-800-465-0234 F

Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com















REFRIGERATION



154" | 32.2" | 32.2" | 33.2" | 34.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.4" | 49.

TECHNICAL SPECIFICATION	
Item	50117
Model	FR-CN-0054-TM
Capacity	43.1 cu. ft. (1220 L)
Maximum Load	88 lbs. (40 kg)
Number of Doors	2 Swing Doors
Number of Shelves	6
Shelf Size	24.4" x 27" (620 x 688 mm)
Shelf Material	Plastic Coated
Exterior Material	Stainless Steel
Number of Casters	4
Power	720W
Amps	7.2A
Electrical	115V / 60Hz / 1Ph
Temperature Controller	Digital
Temperature Range	-22 to -17 °C (-8 to 0°F)
Refrigerant	R290
Max Ambient Temp	37 °C (100 °F)
Insulation Material	Cyclopentane
Defrosting	Automatic
Cooling System	Forced Air
Interior Dimensions (WDH)	49.4" x 27" x 56" (1255 x 688 x 1440 mm)
Net Weight	440 lb. (200 kg.)
Net Dimensions (WDH)	54" x 32.2" x 81.7" (1371 x 818 x 2075 mm)
Gross Weight	523.6 lb. (237.5 kg.)
Gross Dimensions (WDH)	56.5" x 34" x 84.4" (1435 x 865 x 2145 mm)

BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.