



REFRIGERATION

SERVING THE FOOD INDUSTRY SINCE 1951

Aurora White Display Refrigerators, Glass Doors

ITEM: MODEL: RE-

59032 RE-CN-0045E-HC 59033 RE-CN-0009E-HC



22" wide 59033

Attractively display food merchandise and increase impulse sales with Aurora glass door display refrigerators

Glass doors enhance product visibility and draw customer attention. Ideal for supermarkets, cafes, and delis, the Aurora refrigerator combines ample storage with stylish design, enhancing both the aesthetic appeal and functionality of your business.

FEATURES:

- Incredibly Spacious Adjustable Shelves
 This unit is extremely spacious with a large cabinet with multiple adjustable shelves, thus maximizing your commercial kitchen space.
- Powerful, environmentally safe refrigeration system
 Uses R290 refrigerant to keep your ingredients and fully prepared foods at safe temperatures. The compressor is bottom mounted for energy efficiency and also raises the bottom shelf, so all your ingredients are within reach and you don't have to bend as much during loading and unloading.
- Digital Temperature Control
 Easily adjust the cabinet's temperature with the digital temperature controller. The clear LCD readout also helps keep track of the unit's temperature.
- Autodefrost System

This unit has an automatic defrost feature which eliminates the need to spend invaluable time cleaning out the ice.

Telephone: 1-800-465-0234

Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com



















REFRIGERATION

Features	22" wide	54" wide with 45 cu.ft. (1274 L) Capacity
	with 9 cu. ft. (254 L) capacity	and Lightbox
tem	59033	59032
Model	RE-CN-0009E-HC	RE-CN-0045E-HC
Capacity	9 cu. ft. (254 L)	45 cu. ft. (1274 L)
lumber of Doors	1 Swing Door - Glass Door	2 Sliding Door - Glass Door
Self-Closing Door	YES	
Material	Stainless steel interior and exterior, aluminum back	
Number of Shelves	4	8
Shelf Capacity (kg/pc)	88 lb. (40 kg)	
Shelf Material	Plastic Coated	
Number of Casters	NO	
Power	186W	249W
Amps	2.9A	4.3A
lectrical	110-120V / 60Hz / 1Ph	
emperature Controller	Digital	
emperature Range	0.5°C - 5°C (33°F - 41°F)	
efrigerant	R290	
nsulation Material	Cyclopentane	
Cooling System	Ventilated	
Defrosting	Automatic	
nterior Dimensions (WDH)	18.9" x 18.3" x 46" (480 x 465 x 1168 mm)	50"x 28.3" x 62" (1351 x 807 x 2133 mm)
Net Weight	189.5 lb. (86 kg.)	436.5 lb. (198 kg.)
Net Dimensions (WDH)	21.7" x 21.7" x 63" (551 x 551x 1600 mm)	53.2" x 31.8" x 84" (1351 x 807 x 2133 mm)
Gross Weight	225 lb. (102 kg.)	481 lb. (218 kg.)
Gross Dimensions (WDH)	24" x 25" x 69" (599 x 630 x 1755 mm)	56" x 34" x 85" (1422 x 850 x 2148 mm)
Plug Type	NEMA 5-15P	

^{*} This equipment is intended for indoor environment using where ambient temperature do not exceed 24°C(75°F) & 55% relative humidity





REFRIGERATION

TECHNICAL DRAWING (measurements are in mm)



