

Stagionello® Dry Age 3.0 Dry Aging Cabinets

700 LITER · 150 KG

48037 · Standard PI3AION07STI	48038 · 2-Glass View PI3AION07TTI	48039 · 4-Glass View PI3AION074VI
----------------------------------	--------------------------------------	--------------------------------------

900 LITER · 225 KG

48040 · Standard PI3AION09STI	48041 · 2-Glass View PI3AION09TTI	48042 · 4-Glass View PI3AION094VI
----------------------------------	--------------------------------------	--------------------------------------

1400 LITER · 450 KG

48043 · Standard PI3AION14STI	48044 · 2-Glass View PI3AION14TTI	48045 · 4-Glass View PI3AION144VI
----------------------------------	--------------------------------------	--------------------------------------

TWIN 1400 LITER · 150 + 150 KG (2 INDEPENDENT CHAMBERS)

48046 · Standard PI3AIONTWSTI	48047 · 2-Glass View PI3AIONTWTTI	48048 · 4-Glass View PI3AIONTW4VI
----------------------------------	--------------------------------------	--------------------------------------

Patented Italian Dry-Aging Technology — Dry Age Control 3.0, Zero-Cost “Plug & Dry” Installation

Stagionello® Dry Age 3.0 is patented, Italian-made line of dry-aging cabinets, built with automated climate sequencing and pH monitoring to guarantee consistent results. The line spans four capacities — 700L, 900L, 1400L, and a TWIN 1400L with two fully independent chambers — each available as a solid-door Standard cabinet or as a 2-Glass View / 4-Glass View merchandising cabinet for front-of-house display.

Every cabinet runs on the Dry Age Control 3.0 interface with integrated pH reading and monitoring, Dynaflow® thermodynamic air management, and Umiright® automated humidity regulation. Ten climatic recipes are built in — five for dry-aging and five for fresh meat preservation — and an HACCP dual verification system logs temperature, humidity, and pH by date and time throughout the cycle.

Installation is “Plug & Dry” with zero setup cost, using either a tank or a direct water connection, with operator-run self-sterilization between cycles. 20% lower energy use than comparable units and a reduced-plastic design. Every cabinet is AISI 304 stainless steel, cQPSus and FCM certified, carries a 2-Year Parts and 2-Year Labor warranty, and is 100% Made in Italy.

At A Glance — Shared Across the Line

Working / Storage Temperature	-3°C to 35°C / 26.6°F to 95°F
Relative Humidity Range	30% to 99% RH
Control System	Dry Age Control 3.0 — integrated pH reading & monitoring, 10 climatic recipes (5 dry-aging / 5 fresh preservation)
Air & Humidity Management	Dynaflow® thermodynamic airflow · Umiright® humidity regulation
Monitoring & Logging	HACCP dual verification — temperature, humidity, and pH logged by date/time
Construction	AISI 304 stainless steel interior; AISI 304 stainless steel or painted sheet metal exterior
Installation	“Plug & Dry” — zero installation cost, tank or direct water connection, operator self-sterilization
Certifications	cQPSus Certified · FCM Certified
Warranty & Shipping	2-Year Parts · 2-Year Labor · shipped on pallet · Made in Italy

The Line at a Glance



700 Liter Series

48037 Standard · 48038 2-Glass View · 48039 4-Glass View
150 kg max load



900 Liter Series

48040 Standard · 48041 2-Glass View · 48042 4-Glass View
225 kg max load



1400 Liter Series

48043 Standard · 48044 2-Glass View · 48045 4-Glass View
450 kg max load



TWIN 1400 Liter Series

48046 Standard · 48047 2-Glass View · 48048 4-Glass View
150 + 150 kg — 2 independent chambers

Photos shown are the Standard (solid-door) configuration for each size; 2-Glass View and 4-Glass View variants share the same cabinet body with a glazed door.

Technical Specification — 700 Liter			
Item / Model	48037 · Standard	48038 · 2-Glass View	48039 · 4-Glass View
Capacity	700 L / 24.7 cu.ft. — 150 kg max load	700 L / 24.7 cu.ft. — 150 kg max load	700 L / 24.7 cu.ft. — 150 kg max load
Interior (WDH)	620×670×1600 mm	620×660×1600 mm	620×660×1600 mm
Exterior (WDH)	730×785×2115 mm / 28.7"×30.9"×83.2"	730×785×2115 mm / 28.7"×30.9"×83.2"	730×785×2115 mm / 28.7"×30.9"×83.2"
Net / Shipping Weight	225 kg / 265 kg	248 kg / 288 kg	210 kg / 250 kg
Electrical	220–240V/60Hz/1Ph — Max 1730W (8.0A) / Rated 548W (1.9A)	220–240V/60Hz/1Ph — Max 1730W (8.0A) / Rated 548W (1.9A)	220–240V/60Hz/1Ph — Max 1730W (8.0A) / Rated 548W (1.9A)
Doors / Shelves	1 glass swing door · 4 shelves, 35 kg / 77 lb max each	1 glass swing door · 4 shelves, 35 kg / 77 lb max each	1 glass swing door · 4 shelves, 35 kg / 77 lb max each
Temp / Humidity	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH
Certifications	cQPSus Certified · FCM Certified	cQPSus Certified · FCM Certified	cQPSus Certified · FCM Certified
Warranty	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor

Technical Specification — 900 Liter			
Item / Model	48040 · Standard	48041 · 2-Glass View	48042 · 4-Glass View
Capacity	900 L / 31.8 cu.ft. — 225 kg max load	900 L / 31.8 cu.ft. — 225 kg max load	900 L / 31.8 cu.ft. — 225 kg max load
Interior (WDH)	800×660×1600 mm / 31.5"×26"×63"	800×660×1600 mm / 31.5"×26"×63"	800×660×1600 mm / 31.5"×26"×63"
Exterior (WDH)	905×785×2115 mm / 35.6"×30.9"×83.2"	905×785×2115 mm / 35.6"×30.9"×83.2"	905×785×2115 mm / 35.6"×30.9"×83.2"
Net / Shipping Weight	260 kg / 300 kg	290 kg / 330 kg	240 kg / 280 kg
Electrical	220–240V/60Hz/1Ph — Max 2960W (13.4A) / Rated 980W (4.8A)	220–240V/60Hz/1Ph — Max 2960W (13.4A) / Rated 980W (4.8A)	220–240V/60Hz/1Ph — Max 2960W (13.4A) / Rated 980W (4.8A)
Doors / Shelves	1 glass swing door · 4 shelves, 35 kg / 77 lb max each	1 glass swing door · 4 shelves, 35 kg / 77 lb max each	1 glass swing door · 4 shelves, 35 kg / 77 lb max each
Temp / Humidity	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH
Certifications	cQPSus Certified · FCM Certified	cQPSus Certified · FCM Certified	cQPSus Certified · FCM Certified
Warranty	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor

Technical Specification — 1400 Liter

Item / Model	48043 · Standard	48044 · 2-Glass View	48045 · 4-Glass View
Capacity	1400 L / 49.5 cu.ft. — 450 kg max load	1400 L / 49.5 cu.ft. — 450 kg max load	1400 L / 49.5 cu.ft. — 450 kg max load
Interior (WDH)	1350×660×1600 mm / 53"×26"×63"	1350×660×1600 mm / 53"×26"×63"	1350×660×1600 mm / 53"×26"×63"
Exterior (WDH)	1464×875×2115 mm / 57.6"×34.5"×83.2"	1464×875×2115 mm / 57.6"×34.5"×83.2"	1464×875×2115 mm / 57.6"×34.5"×83.2"
Net / Shipping Weight	355 kg / 395 kg	375 kg / 415 kg	335 kg / 375 kg
Electrical	220–240V/60Hz/1Ph — Max 2960W (13.4A) / Rated 980W (4.8A)	220–240V/60Hz/1Ph — Max 2960W (13.4A) / Rated 980W (4.8A)	220–240V/60Hz/1Ph — Max 2960W (13.4A) / Rated 980W (4.8A)
Doors / Shelves	2 glass swing doors · 8 shelves total (4+4), 35 kg / 77 lb max each	2 glass swing doors · 8 shelves total (4+4), 35 kg / 77 lb max each	2 glass swing doors · 8 shelves total (4+4), 35 kg / 77 lb max each
Temp / Humidity	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH
Certifications	cQPSus Certified · FCM Certified	cQPSus Certified · FCM Certified	cQPSus Certified · FCM Certified
Warranty	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor

Technical Specification — TWIN 1400 Liter

Item / Model	48046 · Standard	48047 · 2-Glass View	48048 · 4-Glass View
Capacity	1400 L total — 2 chambers, 150 kg max load each	1400 L total — 2 chambers, 150 kg max load each	1400 L total — 2 chambers, 150 kg max load each
Interior (WDH)	2 × 570×660×1600 mm per chamber / 2 × 22.4"×26"×63"	2 × 570×660×1600 mm per chamber / 2 × 22.4"×26"×63"	2 × 570×660×1600 mm per chamber / 2 × 22.4"×26"×63"
Exterior (WDH)	1464×875×2115 mm / 57.6"×34.5"×83.2"	1464×875×2115 mm / 57.6"×34.5"×83.2"	1464×875×2115 mm / 57.6"×34.5"×83.2"
Net / Shipping Weight	395 kg / 445 kg	425 kg / 485 kg	365 kg / 405 kg
Electrical	220–240V/60Hz/1Ph — Max 3500W (15.0A) / Rated 1300W (5.9A)	220–240V/60Hz/1Ph — Max 3500W (15.0A) / Rated 1300W (5.9A)	220–240V/60Hz/1Ph — Max 3500W (15.0A) / Rated 1300W (5.9A)
Doors / Shelves	2 glass swing doors, 1 per chamber · 8 shelves total (4+4), 35 kg / 77 lb max each	2 glass swing doors, 1 per chamber · 8 shelves total (4+4), 35 kg / 77 lb max each	2 glass swing doors, 1 per chamber · 8 shelves total (4+4), 35 kg / 77 lb max each
Temp / Humidity	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH	-3°C to 35°C (26.6°F to 95°F) · 30% to 99% RH
Certifications	cQPSus · FCM · EFSA Compliant	cQPSus · FCM · EFSA Compliant	cQPSus · FCM · EFSA Compliant
Warranty	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor	2-Year Parts · 2-Year Labor