*SERVING THE FOOD INDUSTRY SINCE 1951*

# Aurora Refrigerated Pizza Prep Tables

| | | |
|---|---|---|
| ITEM: | 59042 | 59043 |
| MODEL: | PT-CN-1270E-HC | PT-CN-1829E-HC |

45" wide
59042

67" wide
59043

## Aurora Refrigerated Pizza Prep Table helps you create your signature pizzas, sandwiches and salads quickly and easily.

This refrigerated prep table line boasts a spacious working area, allowing for extra ingredient storage. The refrigeration system keeps food at safe temperatures between 0.5°C to 4.4°C (33°F and 40°F). Also, it uses Hydro-Carbon R290 refrigerant, so it's environmentally friendly and energy-efficient. High-quality stainless steel construction provides durability and longevity and guarantees maximum hygiene and food-grade standards.

**FEATURES:**

- Stainless steel exterior, aluminum back
- Refrigeration system keeps food at safe temperatures between 0.5 - 4.4°C (33°F and 40°F)
- Self-closing doors with 90 degree stay-open feature
- Adjustable heavy-duty PE coated shelves
- Cutting board thickness: 0.6 inch / 15 mm
- R290 refrigerant – environment friendly and more efficient

**2 YEARS WARRANTY**
2 YEARS PARTS AND LABOUR
5 YEARS ON COMPRESSOR

ETL Intertek     ETL Intertek

NEMA
5 - 15P
125VAC / 15 AMP

Authorized Dealer

MADE IN CHINA

## TECHNICAL SPECIFICATION

| Features | 45" wide with 7.8 cu.ft. capacity | 67" wide with 15.6 cu.ft. capacity |
|---|---|---|
| Item | 59042 | 59043 |
| Model | PT-CN-1270E-HC | PT-CN-1829E-HC |
| Capacity | 7.8 cu.ft. (220 L) | 15.6 cu.ft. (442 L) |
| Number of Doors | 1 | 2 |
| Number of Pans | 12 x 1/6 pans OR 6 x 1/3 pans | 18 x 1/6 pans OR 9 x 1/3 pans |
| Number of Shelves | 1 | 2 |
| Shelf Material | Plastic Coated | |
| Shelf Capacity | 88 lb. (40 kg.) | |
| Number of Casters | Yes (4) | |
| Power | 336 W | 552 W |
| Amps | 3.36 A | 5.52 A |
| Electrical | 110V / 60Hz / 1Ph | |
| Temperature Controller | Digital | |
| Temperature Range | 0.5°C - 4.4°C (33°F - 40°F) | |
| Refrigerant | R290 | |
| Insulation Material | Cyclopentane | |
| Cooling System | Ventilated | |
| Defrosting | Automatic | |
| Interior Dimensions (WDH) | 22.3" x 23.2" x 22.9" (566 x 590 x 582 mm) | 45" x 27.2" x 22.9" (1143 x 690 x 582 mm) |
| Net Weight | 187 lb. (85 kg.) | 244.7 lb. (111 kg.) |
| Net Dimensions (WDH) | 44.5" x 31.5" x 39.4" (1131 x 800 x 1002 mm) | 67.3" x 31.5" x 39.4" (1709 x 800 x 1002 mm) |
| Gross Weight | 265 lb. (120 kg.) | 355 lb. (161 kg.) |
| Gross Dimensions (WDH) | 54" x 36" x 46" (1380 x 920 x 1160 mm) | 76" x 37" x 48" (1920 x 920 x 1160 mm) |
| Plug Type | NEMA 5-15P | |

*\* This equipment is intended for indoor environment using where ambient temperature do not exceed 24°C(75°F) & 55% relative humidity*

## TECHNICAL DRAWING (measurements are in mm)



ELEVATION

PLAN

SECTION VIEW

**45" wide
59042**

1131
1092
944
800
448
496
15
50
890
1002
1411
650



ELEVATION

PLAN

SECTION VIEW

**67" wide
59043**

20
1709
722
45
902
944
800
448
496
15
50
890
1002
1366
605