



SERVING THE FOOD INDUSTRY SINCE 1951

Refrigerated Display Case with Four-Sided Glass

ITEM:	44471	44472	44473	44474
MODEL:	RS-CN-0270-L	RS-CN-0350	RS-CN-0400-T	RS-CN-0550

Attractively display food merchandise and increase impulse sale with maximum product visibility.

Omcan's Refrigerated Display Case provides an economical solution for displaying your products. Featuring a brilliant internal LED illumination on sides as well as stainless steel exterior, this refrigerated display case also has an adjustable chrome plated shelves, digital temperature controller and display, automatic defrost, and ventilated cooling system.



44471 - 26" Wide / 59" Tall



44473 - 26" Wide / 75" Tall



44472 - 33" Wide / 59" Tall





44474 - 33" Wide / 75" Tall

Telephone: 1-800-465-0234

Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com



Authorized Dealer

TECHNICAL SPECIFICATION

Features	26" Wide - 59" Tall with 270L capacity	26" Wide- 75" Tall with 400L capacity	33" Wide- 59" Tall with 350L capacity	33" Wide- 75" Tall with 550L capacity
Item	44471	44473	44472	44474
Model	RS-CN-0270-L	RS-CN-0400-T	RS-CN-0350	RS-CN-0550
Capacity:	270 L / 9.53 cu. ft.	400 L / 14.13 cu. ft.	350 L / 12.36 cu. ft.	550 L / 19.42 cu. ft.
Number of Shelves:	2	3	2	3
Shelve Size:	17.8" x 20.3"	17.8" x 20.3"	25.7" x 20.3"	25.7" x 20.3"
Rated Current	2.8 A	2.8 A	2.8 A	2.8 A
Power:	475 W	495 W	640 W	500 W
Lamp Power	10 W	16.8 W	10 W	16.8 W
Electrical:	110V / 60Hz / 1Ph	110V / 60Hz / 1Ph	110V / 60Hz / 1Ph	110V / 60Hz / 1Ph
Temperature Range:	2°C - 10°C / 35.6°F - 50°F	2°C - 10°C / 35.6°F - 50°F	2°C - 10°C / 35.6°F - 50°F	2°C - 10°C / 35.6°F - 50°F
Refrigerant & Injection:	R290 & 110g	R290 & 110g	R290 & 110g	R290 & 110g
Blowing Gas	C5H10	C5H10	C5H10	C5H10
Weight:	308.6 lbs / 140 kg	385.8 lbs / 175 kg	335 lbs / 152 kg	423.3 lbs / 192 kg
Gross Weight:	363.76 lbs / 165 kg	452 lbs / 205 kg	399 lbs / 181 kg	500 lbs / 227 kg
Dimensions (WDH):	25.6" x 25.6" x 59"	25.6" x 25.6" x 75"	33.46" x 25.6" x 59"	33.46" x 25.6" x 75"
Gross Dimensions (WDH):	29.5" x 29.5" x 65"	29.5" x 29.5" x 81"	37.36" x 37.36" x 65"	37.36" x 29.5" x 81"

TECHNICAL DRAWING

