



SERVING THE FOOD INDUSTRY SINCE 1951

Refrigerated Pizza Prep Table

ITEM: 50042
MODEL: PT-CN-1270-HC

50043
PT-CN-1829-HC

50044
PT-CN-2337-HC



50" Wide
50042



71" Wide
50043



92" Wide
50044

Refrigerated Pizza Prep Table helps you create your signature pizzas, sandwiches and salads quickly and easily.

This refrigerated prep table line boasts a spacious working area, allowing for extra ingredient storage. The refrigeration system keeps food at safe temperatures between 0.5°C to 4.4°C (33°F and 40°F). Also, it uses Hydro-Carbon R290 refrigerant, so it's environmentally friendly and energy-efficient. High-quality stainless steel construction provides durability and longevity and guarantees maximum hygiene and food-grade standards. Small size countertop refrigerated display glass door merchandiser, ideal for promotions or impulse new products. Designed for places with limited space.

FEATURES:


- Stainless steel exterior, aluminum back
- Refrigeration system keeps food at safe temperatures between 0.5 - 4.4°C (33°F and 40°F)
- Self-closing doors with 90 degree stay-open feature
- Adjustable heavy-duty PE coated shelves
- Cutting board thickness: 0.6 inch / 15 mm
- R290 refrigerant – environment friendly and more efficient

Telephone: 1-800-465-0234

Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com



Authorized Dealer

(Version 2024.07)

Page 1 / 3

TECHNICAL SPECIFICATION

Features	50" wide with 13.8 cu.ft (391 L) Capacity	71" wide with 16.9 cu.ft (478 L) Capacity	92" wide with 24.2 cu.ft (684 L) Capacity
Item	50042	50043	50044
Model	PT-CN-1270-HC	PT-CN-1829-HC	PT-CN-2337-HC
Capacity	13.8 cu.ft (391 L)	16.9 cu.ft (478 L)	24.2 cu.ft (684 L)
Number of Doors	1	2	3
Number of Pans	6 x 1/3 pans	9 x 1/3 pans	12 x 1/3 pans
Number of Shelves	1	2	3
Shelf Material	Plastic Coated		
Shelf Capacity	73 lbs (33 kg)	64 lbs (29 kg)	61.7 lbs (28 kg)
Number of Casters	4	4	6
Power	1/6 HP	1/5 HP	1/4 HP
Amps	2.64 A	3.42 A	5.28 A
Electrical	110V / 60 Hz / 1 Ph		
Temperature Controller	Digital		
Temperature Range	0.5°C - 4.4°C (33°F - 40°F)		
Refrigerant	R290		
Insulation Material	Cyclopentane		
Cooling System	Ventilated		
Defrosting	Automatic		
Interior Dimensions (WDH)	27.4" x 22.8" x 26.2" (696 x 580 x 665 mm)	48.4" x 22.8" x 26.2" (1229 x 579 x 665 mm)	69.45" x 22.83" x 26.18" (1764 x 579 x 664 mm)
Net Weight	374 lbs. (170 kg)	431 lbs. (196 kg)	565 lbs. (257 kg)
Net Dimensions (WDH)	49.9" x 31.5" x 42.9" (1266 x 800 x 1088 mm)	70.9" x 31.5" x 42.9" (1800 x 800 x 1088 mm)	91.9" x 31.5" x 42.9" (2334 x 800 x 1088 mm)
Gross Weight	497 lbs. (226 kg)	563 lbs. (256 kg)	719 lbs. (327 kg)
Gross Dimensions (WDH)	54" x 37" x 46" (1380 x 920 x 1160 mm)	76" x 37" x 46" (1920 x 920 x 1160 mm)	97" x 37" x 46" (2450 x 920 x 1160 mm)
Plug Type	NEMA 5 - 15 P		

TECHNICAL DRAWING

