



MEAT SLICERS

S SERIES HORIZONTAL GEAR-DRIVEN SLICERS - 12.3", 14" & 15" BLADE

Item: 44006/ 39631/ 38915/ 49532


Model: MS-IT-0313-H/ MS-IT-0350-H/ MS-IT-0370-H/ MS-IT-0370-H-R











MEAT SLICERS S SERIES HORIZONTAL GEAR-DRIVEN SLICERS

12.3", 14" & 15" BLADE



OMAS "S" SERIES SLICERS

They are especially designed to cut fresh meat. The large horizontal carriage has a double sliding table, specifically designed to cut fresh meat by providing a long stroke depth. The high performance gear driven motor offers a constant blade speed throughout the cut, for precision slicing. The carriage rolls easily on ball bearings and the anodized aluminium body provides easy cleaning. Our "S" Series slicers can be cleaned without tools. The carriage, end grip, and blade cover are easily removable. The machine is made of anodized aluminium alloy, which is resistant to food-acids. The smooth finish is durable and easy to clean. The flow line design and the rounded corners of the polished anodized aluminium body makes the after use cleaning easy. The high carbon steel, hard chromed blade has a hollow ground taper that permits sharpening for full life of the blade and to facilitate the penetration and the slice detachment.



- Superglide: Specially treated gauge-plate and blade cover for a smoother performance that ensures precision cuts at all times
- Additional safety features: Fixed blade ring guard; aluminium thumb guard; interlock for carriage disassembly; NVR (No Voltage Release) switch and protections on the sharpener and blade
- In Compliance With Province Of Quebec Safety Standards (Item 39631 & 38915 Only)
- New Design: Enlarged receiving surface (Item 38915 and 49532 Only)

DETAIL IMAGES



Superglide



Built-in sharpener



Interlock for carriage disassembly



Control Pushbutton (no-voltagerelease switch)



Ring guard



Aluminium thumb quard



Ergonomically designed for easy cleaning



Slice thickness control

OMCAN INC.

1-800-465-0234 ax: (905) 607-0234 mail: sales@omcan.com ebsite: www.omcan.com





Follow us to keep up to date with the latest news and offers









MEAT SLICERS


S SERIES HORIZONTAL GEAR-DRIVEN SLICERS 12.3", 14" & 15" BLADE

CUT THICKNESS



TECHNICAL SPECIFICATION


12.3" Horizontal Gear-Driven Slicer (MS-IT-0313-H)



Technical Specification							
ITEM NUMBER	44006	RPM	250				
MODEL	MS-IT-0313-H	VOLTAGE	110V/60/Hz/1				
BLADE	12 5/16"/313mm	WEIGHT	84 lbs/ 38 kg				
POWER	0.40 HP / 0.30 kW	GROSS WEIGHT	101 lbs/ 46 kg				
CHEESE SLICING†	mil	DIMENSIONS (WDH)	29"x26"x20"/ 737x440x508 mm				
SLICING VOLUME*	8 hours or more	GROSS DIMENSIONS	33"x28"x27"/ 838x711x686 mm				
CUTTING SIZE	10.63"x8.86"/ 270x225 mm	ADDITIONAL INFORMATION					


0-25mm

14" Horizontal Gear-Driven Slicer (MS-IT-0350-H)



Technical Specification						
ITEM NUMBER	39631	RPM	250			
MODEL	MS-IT-0350-H	VOLTAGE	110V/60/Hz/1			
BLADE	14"/350mm	WEIGHT	110 lbs/ 50 kg			
POWER	0.40 HP / 0.30 kW	GROSS WEIGHT	112 lbs/ 51 kg			
CHEESE SLICING [†]	mil	DIMENSIONS (WDH)	26"x28"x21.7"/ 660x711x551 mm			
SLICING VOLUME*	8 hours or more	GROSS DIMENSIONS	34"x31"x26"/ 863x787x660 mm			
CUTTING SIZE	12.2" x 9.84"/ 310x205 mm	ADDITIONAL INFORMATION	In compliance with Province of Quebec safety standards			
CUT THICKNESS	0-25mm					

15" Horizontal Gear-Driven Slicer (Red/Silver) (MS-IT-0370-H)/ (MS-IT-0370-H-R)



Technical Specification						
ITEM NUMBER	38915 / 49532	RPM	250			
MODEL	MS-IT-0370-H/ MS-IT-0370-H-R	VOLTAGE	110V/60Hz/1			
BLADE	15/370mm	WEIGHT	125 lbs/ 56.7 kg			
POWER	0.40 HP / 0.30 kW	GROSS WEIGHT	140 lbs/63.5 kg			
CHEESE SLICING†	••••	DIMENSIONS (WDH)	31.5"x29.5"x22"/800x749x559 mm			
SLICING VOLUME*	8 hours or more	GROSS DIMENSIONS	36"x34"x27"/ 914x864x686 mm			
CUTTING SIZE	14.56" x 10.23"/ 370x260 mm	ADDITIONAL INFORMATION	In compliance with Province of Quebec safety standards			
CUT THICKNESS	0-25mm					











OMCAN INC.

none: 1-800-465-0234 Fax: (905) 607-0234 E-mail: sales@omcan.com Vebsite: www.omcan.com















^{*} Results may vary due to product consistency and temperature