



VACUUM PACKAGING

TURBOVAC TOP VACUUM PACKAGING MACHINE

Item: 59006
Models: VP-NL-0004-SN

Item: 59007
Models: VP-NL-0008-SN

Item: 59008
Models: VP-NL-0016-SN

Item: 59009
Models: VP-NL-0021-SN


Item: 59010
Models: VP-NL-0016-LN

“PLUG AND PLAY”


Our 4 table top machines have all the quality engineering and build of our industrial vacuum machines. Constructed with Busch pump.



VP-NL-0004-SN / VP-NL-0008-SN Configuration



VP-NL-0016-SN / VP-NL-0021-SN / VP-0016-LN Configuration



Item might not be exactly as shown



WARRANTY
PARTS AND LABOR



Authorized Dealer

Turbovac Redefining The Benchmark For Vacuum Packaging Machines

Turbovac offers a full range of vacuum packaging machines: reliable, robust, and easy to service and maintain. Turbovac recently redesigned its complete range of vacuum packaging machines and made them even easier to operate and clean. The full range of machines and available options makes it easy to select exactly the right solution for your packaging needs.

All models have hygienic easy-to-clean vacuum chambers and easily removable seal beams and silicon bars. An intuitive digital control unit can automatically detect the optimum vacuum level for each product. And for products with a high moisture content, the control unit retains exactly the right amount of moisture. This improves the tenderness and flavour of the products. With an ingenious redesign focusing on functionality, Turbovac is now setting the standard for quality and design in the industry.

New Digital Control Unit with LCD DISPLAY



The professional machines are standard equipped with a digital LCD control unit with 10 programs. The more advanced machines are equipped with a 10 program sensor control system which actually measures the vacuum in the vacuum chamber. The time controlled machines can easily be converted into sensor controlled machines later on. The sensor measures evaporation when moist products or liquids, like sauces, are being packed. At this optimum point moisture is extracted from the product causing it to dry out, loose weight or start bubbling and spilling over. The sensor detects this point immediately as being the optimum level where all air and oxygen has been removed and continues the cycle by sealing the package.

OPTIONAL FEATURES (For 10 program machines)

Sensor/Time control

- With a sensor controlled machine the vacuum is measured with a sensor with very high accuracy and the results are digitally displayed
- With a time controlled vacuum machine a time is set and the vacuum level can be monitored with an analogue vacuummeter

Soft Air

The Soft Air program slowly brings the airpressure in the machine back to atmospheric level. This allows the plastic to wrap and stretch around sharp edges of the product which might otherwise puncture the plastic bag. Fragile products will keep in the right form when Soft air is added.

Modified Atmospheric Packaging (M.A.P - Gas flush)

Some products cannot be packaged under vacuum but may better packaged by replacing the air by a mix of gases, like the Inert gas Nitrogen (N₂), Carbondioxide (Co₂) or Oxygen (O₂) to increase shelf life and appearance.

TECHNICAL SPECIFICATION	11" Seal Length with 4 m ³ Vacuum Pump	11" Seal Length with 8 m ³ Vacuum Pump	16 1/2" Seal Length with 16 m ³ Vacuum Pump	16 1/2" Seal Length with 21 m ³ Vacuum Pump	16 1/2" Seal Length / Two Seal bar with 16 m ³ Vacuum Pump
ITEM NUMBER	59006	59007	59008	59009	59010
MODEL	VP-NL-0004-SN	VP-NL-0008-SN	VP-NL-0016-SN	VP-NL-0021-SN	VP-NL-0016-LN
SEAL LENGTH	11"/280mm	11"/280mm	16.53"/420mm	16.53"/420mm	16.53"/420mm (x2)
VACUUM PUMP	4 m ³	8 m ³	16 m ³	21 m ³	16 m ³
10 PROGRAMMABLE CONTROL	NO	NO	NO	YES	NO
MAXIMUM PRODUCT HEIGHT	4.33"/110mm	4.33"/110mm	7"/180mm	7"/180mm	
USEFUL CHAMBER SIZE (DWH)	12.20" x 11" x 4.33"	12.20" x 11" x 4.33"	14.56" x 16.53"(max) x 7"	14.56" x 16.53"(max) x 7"	
POWER CONSUMPTION (kW)	0.4-0.5	0.4-0.5	0.7-1.3	0.7-1.3	
ELECTRICAL	100-120V/60Hz/1	100-120V/60Hz/1	100-120V/60Hz/1	100-120V/60Hz/1	
NET WEIGHT	25 kg / 55 lbs.	25 kg / 55 lbs.	60 kg / 132 lbs.	60 kg / 132 lbs.	
DIMENSIONS (DWH)	19.68" x 14.37" x 13.38"	19.68" x 14.37" x 13.38"	21.85" x 20.66" x 18.11"	21.85" x 20.66" x 18.11"	

Available Options: 2 Filler Plates (20mm each), Sensor (only available for unit with 10-Program Control)

OMCAN INC.

Telephone: 1-800-465-0234
 Fax: (905) 607-0234
 E-mail: sales@omcan.com
 Website: www.omcan.com



Follow us to keep up to date with the latest news and offers

